

Control is at your equipment operator's fingertips with a ProComm embedded control unit and a TriggerPad handstation.



ProComm 100

This system makes it easy to add a wireless operator handheld to your machine or process control equipment.



TriggerPad 100

TriggerPad 105

ProComm Features

- 8 isolated relay outputs, 120VAC, 6A, NO or NC
- Relay life of 1 million cycles
- 2 isolated discrete inputs, 120VAC/DC
- 1 analog output, 0 -10VDC
- RS232 serial port for programming
- Removable screw terminal connectors
- Output active and status indicators
- Power and data indicators
- 900MHz one way radio with 8 channels (license free)
- Range of 300 feet typical
- CRC data error checking
- Rugged aluminum enclosure
- Customized logic programming available
- Dimensions: 8" X 4.125" X 4", 3 lb.
- Power: 100VAC to 240VAC, 50Hz or 60Hz
- Remote antenna mount up to 30 feet

TriggerPad Features

- 1 million cycle sealed mechanical tactile pushbuttons
- Red, black, green, blue, and yellow switches available
- Eight button membrane switch available with 2 digit LED
- Custom labeling and switchpads available with up to 12 switches
- Temperature range: 0 °C to +70°C
- Storage temperature range: -40°C to +85°C
- Dimensions: 2.75" X 1.375" X 7", 12.5 oz.
- Power: 3AA batteries (32 hours cont. operation)
- Multiple operator capability
- Sealed handheld enclosure

Stand Alone or PLC Systems

